

SURFACE COLLECTION


TOUCH

ULTIMATE HIGH DEFINITION STRUCTURED PANELS

With high-definition appearance and a surface texture that mimics real wood, TOUCH panels are the deepest structured thermo fused laminate panels produced in North America. Durable and extremely low maintenance, TOUCH panels feature excellent hardness, scratch and wear resistance as well as a budget-friendly price. Available in 8 textured wood grain colors, TOUCH panels enhance any space with the strength, texture and aesthetic of natural materials.

SPECIFICATIONS

- **Core Thickness:** 3/4" Western Pine particlboard with a deep textural melamine top and bottomlayer.
- **Panel Size:** 4' x 8' max or cut to size
- **Colors and Edgebanding:** 8 different wood grain colors to choose from with 8 matching edgebanding options. (See below)



Designer White




Cortez



Silverton



Durango



Vail



Slate



Basalt



Black

KEY FEATURES

- **Structured Melamine:** thermo fused laminate have the appearance of real wood made by heat and pressure.
- **Extremely Durable:** finest-quality melamine fused to Western Pine industrial core.
- **Panel to Panel Consistency:** manufactured to ensure color, surface and core qualities are consistent.

MAINTENANCE

To maintain TOUCH panels, gently clean, do not scrub, with a clean, soft, lint-free cloth and water. Best results will be achieved using a micro-fiber cloth or chamois, and if necessary, a non-abrasive soap or detergent. Do not use brushes, scourers or scrapers.

INSTALLATION RECOMMENDATIONS

TOUCH panels are intended for dry interior vertical applications. All mounting areas should be clean and free of debris. There are a variety of installation methods that can be used. It is the responsibility of the purchaser to understand the site conditions and install according to those conditions. Installation guides and hardware options can be found at www.soelbergi.com

STORAGE

TOUCH panels should be stored in an interior HVAC controlled environment. Store panels horizontally and panels should be well supported at all times in the original shipping crate. Panels are supplied with a protective film, which should not be removed until the installation and project are complete. Ensure panels with masking film are not stored in direct sunlight as the film could be affected and difficult to remove.

MATERIAL HANDLING

TOUCH panels should be handled with care and supported at all times. Do not allow any hard or abrasive materials or surfaces to come in contact with TOUCH panels.